

Z6MK3

KA-BAND COMMUNICATION

Z _SERIES
SUPERTRACK

The SuperTrack Z-Series is the perfect solution for ships looking for broadband speeds at sea. Stay in touch with your networks via high speed access to the internet, email, multiple VoIP phones and more.



STANDARD FEATURES

- **Web interface & Remote software Upgrade available**
- **Simplicity**
Integrated into one module from Motor Driver, RF control module, PCU
- **Automatic Satellite Search & Skew Control**
- **Unlimited Azimuth & Brake System**
- **Accurate Signal Acquisition by KNS's Distinctive Algorithm**
- **Pre-programmed Satellite Database**
Editable 80 satellite data
- **Antenna Control Unit**
3 Types of Gyro Input (NMEA, Synchro, Step by Step)

ABOVE DECK

Dish Diameter	60cm(24")
Antenna Dimension	102cm(D) x 104cm(H)
Antenna Weight	70 Kg
Radome Material	Honeycomb FRP
Frequency	TX : 29.0~31.0 GHz RX : 19.2~21.2 GHz
Antenna Gain	TX : 42.9 dBi @ 30.0 GHz RX : 39.8 dBi @ 20.2 GHz
G / T	15.97 dB/K (in Radome) @ 30deg. Elevation angle and 20.2GHz, Clear Sky
Operating Platform	3 - Axis
LNB	Single PLL / Universal LNB (Optional)
BUC	4W / 6W / 8W / 16W (optional)
Skew Control	Automatic
Elevation Angle	-10° to +100°
Azimuth Range	Unlimited
Cross Angle	± 35°
Ship Motion	Roll : ±20° at 8-12 sec periods Pitch : ±10° at 6-12 sec periods Yaw : ±8° at 15-20 sec periods
Tracking Speed	More than 90°/sec
Vibration Damper	Rubber Damper included
Temperature	-20°C to +55°C
Humidity	Up to 100% @ 40°C
Antenna Input Power	48V DC, 4.18A

BELOW DECK

ACU Size	19" Rack 1U size
Gyro Interface	NMEA 0183, Synchro, Step by Step
Input Power	100~120V AC / 200~240V AC, 50/60Hz, 8A/4A
Output Power	48V DC, 4.18A
External I/O	RS-232C, Mini-USB, Ethernet, Console

PACKING

Packed by	Wooden Crate
------------------	--------------

WARRANTY INFORMATION

KNS offers 2-year parts, 1-year onboard labour warranty for the SuperTrack series

* This Specification can be changed without notice.